













# HOSES

## MATERIAL EPDM



Part No.	D1	D	L (m)	Colour	Working Pressure (Bar)	Burst Pressure (Bar)	Bend Radius	
E10B	10	16,5	50		15	60	60	1
E10R	10	16,5	50		15	60	60	1
E10S	10	16,5	50		15	60	60	1
E13B	13	21	50		15	60	90	1
E13R	13	21	50		15	60	90	1
E13S	13	21	50		15	60	90	1
E19B	19	27	30		15	60	110	1
E19R	19	27	30		15	60	110	1
E19S	19	27	30		15	60	110	1

### Tube:

Black, antistatic, smooth EPM Nitrosamine free rubber compound, resistant to heat, hot water and water vapour.

### Reinforcement:

Synthetic textile yarns.

### Cover:

Blue, Red, or Black smooth EPDM Nitrosamine free rubber compound. Resistant to abrasion, ozone, heat, and weather.

### Applications:

Flexible hose designed for hot water and water vapour for mould temperature controlling.

### Temperature range:

Working temperature:  
Up to +140°C (+284°F)  
Peak up to +164°C (+327°F).

Note: Lifetime of this hose will be substantially reduced if operating temperatures exceed +130°C (+266°F).

### Tolerances:

UNI EN ISO 1307/97 tolerances for inside diameters up to and including 25 mm.

### On inside diameter:

For I.D. 5.1 up to 20 mm  $\pm$  0.80 mm.  
Length tolerance:  $\pm$  1%.