

MOULD LUBRICANT

MAINTENANCE LUBRICANT



Technical Description:

The mould lubricant is a multi-purpose product for lubricating, cleaning, dewatering, penetrating and corrosion protection. It is a high performance, PTFE reinforced lubricant with strong penetrating and extreme pressure properties. This product also possesses strong water displacing properties

Can be used in endless applications on all metallic surfaces including moulds, chains, gears, tools, locks, etc.

Not suited for use on decorative substrates, where coatings may be affected. If used on thermoplastics, please first apply on a test area and assess if the lubricant is appropriate based on the results.

Application details:

Shake thoroughly before use. Spray directly onto the component, from a distance of 20-30 cm, ensuring even coverage. Use the extension tube for areas of difficult accessibility.

Properties:

Operating Temperature	Up to 60°C
Maximum intermittent temperature	100°C
Specific gravity	0.875 +/- 0.015
Appearance	Hazy mid/dark brown liquid
Viscosity	Thin liquid
Non Volatiles % m/m	70-80
Active Content % m/m, as Supplied	70-80
Flammability, as Supplied	Extremely flammable
Flashpoint	-20°C
Expiration date	24 months under original seal and proper storage conditions

Composition data:

A solution of refined mineral oils, sarcosine and imidazoline surfactants, and PTFE in white spirit and n-butyl acetate, in butane/isobutene/propane propellant.